REPLACEMENT FOR T STYLE CELLS



| Part # | DESCRIPTION | OUTPUT | | QTY PLATES |
|------------|-------------------------------------|--------|------------|------------|
| | | G/HR | LBS/ 24HRS | / BLADE |
| T-CELL5-U | REPLACEMENT FOR T-CELL 5 SALT CELL | 15.0 | 0.79 | 7 |
| T-CELL9-U | REPLACEMENT FOR T-CELL 9 SALT CELL | 20.0 | 0.90 | 13 |
| T-CELL15-U | REPLACEMENT FOR T-CELL 15 SALT CELL | 30 | 1.45 | 13 |

DESIGNED AND ENGINEERED IN AUSTRALIA BY THE SALT WATER SPECIALISTS SINCE 1992.

REPLACEMENT FOR LM & EI CELLS

High impact Acrylic

High output cell material

Designed as a direct replacement for easy installation



FEATURES

- IMPROVED DESIGN AND FLOW
- ENGINEERED FOR LONGEVITY
- PREMIUM 1 MM ELECTRODE PLATE/BLADE
- RESIN FILLED END
- FULLY SEALED ELECTRODE CONNECTIONS
- QUALITY COMPONENTS
- 2 YEAR WARRANTY

| Part # | DESCRIPTION | OUTPUT | | QTY PLATES |
|-----------|------------------------------|--------|------------|------------|
| | | G/HR | LBS/ 24HRS | / BLADE |
| LM-24-G-U | REPLACEMENT FOR LM SALT CELL | 24.0 | 1.27 | 7 |
| El35-G-U | REPLACEMENT FOR EI SALT CELL | 25.0 | 1.32 | 11 |

©2021 CAS|Crystal Aquatic Systems. All rights reserved. Unauthorized reproduction is prohibitted by law. While every effort is made in maintaining the accuracy of the information contained in this brochure the same information is subject to change by circumstances out of our control at the discretion of management without further notice.



